



PROVIDING TWO YEAR WARRANTY FOR MAIN COMPONENTS (EASILY WORN PARTS EXCLUDED)



Pump Manifold and Filter Screen for less pressure pulse and fluid filtering.




Stainless Steel Fluid Section, durable, lightweight, rust proof, and easily disassembled.



Electronical Pressure Control with Digital Display



Self-locking mechanism, easy to take out the coating bucket.



With Coating Bucket Hook, easy to move around with no need to take out the bucket.

Applications:

1. Latex, normal paint, acrylic paint, polyester, lacquer.
2. Waterproofing material (A/B two component polyurethane, mixed together, finish painting within 30 minutes)
3. Oil-based & water-based fireproofing material (about 1mm thickness each layer)
4. Flooring epoxy paint
5. Water-based epoxy zinc-rich material (the zinc particle must be small size, and the fluid need to be mixed always)

Technical Data:

Voltage: 220 ~ 240 Volt AC, 50/60 Hz, 110V/60HZ

Motor Output Power: 1800W

Pressure Control: Electronical + Digital Display

Max. Flow Rate: 3.8 L/min

Max. Tip Size (1 gun): 0.031"

Max. Tip Size (2 guns): 0.021"

Max. Spraying Pressure : 120bar/1740psi (0.031");

150bar/2175psi (0.029")

G.W. / N.W.: 48.9/39.7kgs

Package: 64*58*84cm carton box.

Standard Accessories in Package:

- Machine 1pcs
- Spray Gun(with 2 tips and tip guard) 1pc
- High Pressure Hose(15m) 1pc
- 45cm Extension Pole 1pc
- Lubrication Oil 1pc
- Repair Tools 1set
- Manual 1pc